CH - CA and MH - MA enclosures

inserts: page CDD 42 poles + 🕀 55 CQE 18 poles + ⊕ 75 CN 10 poles + 🖶 81 CCE 10 poles + 🖶 88 CNE, CSE..... 10 poles + ⊕ 89 CSS 10 poles + 🕀 100 114 CMCE 3+2 (aux) poles + 🖶 114 129 137÷151

insert centre distance: 57 x 27 mm

57.27

size

The covers for C, G and LG versions cannot be used together with coding pins. If this application is required, please contact ILME SpA.



dimensions indicated are not binding and may be changed without notice






size "57.27" standard version


description	part No.	entry Pg	part No.	entry M	part No.
with levers, side entry ¹⁾ with levers, side entry ¹⁾ with levers, side entry, high construction ¹⁾ with levers, side entry, high construction ¹⁾	CHO 10 X CAO 10 X CAO 10 X29	16 21 29	MHO 10 X20 MHO 10 X25 MAO 10 X32 MAO 10 X40	20 25 32 40	
with levers, top entry ¹⁾ with levers, top entry ¹⁾ with levers, top entry, high construction ¹⁾ with levers, top entry, high construction ¹⁾	CHV 10 X CAV 10 X CAV 10 X29	16 21 29	MHV 10 X20 ** MHV 10 X25 MAV 10 X32 MAV 10 X40	20 25 32 40	
with 4 pegs (for housings with 2 levers and gasket) with 4 pegs and gasket (for housings with 2 levers) ^a with 2 pegs (for housings with 1 lever and gasket)					CHC 10 CHC 10 C CHC 10 L
with 2 levers (for hoods with 4 pegs) with 1 lever (for hoods with 2 pegs)					CHC 10 G CHC 10 LG
 ¹⁾ May be combined with hoods: - CHI/CHP/CAP 10 CS/CP/C - MHP/MAP 10 CS/CP 	dimensions in mm CHO X (CAO X) and MHO X (MAO X)			dimensions in mm CHC	




- CHO/CAO 10 X and CHV/CAV 10 X

- MHO/MAO 10 X and MHV/MAV 10 X
- ** can only be used with a complete cable clamp (to be purchased separately)





CHV X (CAV X) and MHV X (MAV X)





0



снс с






CHC L



12 43

CHC G



CHC LG



